# Model NO. C10-CP,C10-GD,C10-CW C10-GW

### 10dBm dual wide band consumer repeater

## > Introduction



- ► The consumer repeater from Amplitec is an ideal solution for providing a cost effective improvement in cellular in-building coverage of a home, office, restaurant or building, in the quickest time possible, on any of CDMA, GSM850, GSM900, GSM1800, GSM1900, and WCDMA.
- ► To maintain safe and specific output signal levels and give alarms on self-oscillation, the repeater has built-in AGC and ALC circuits, which can automatically control the gain of the repeater depending upon the strength of input signals.
- Wide band feature enables all devices operating within the wide frequency range of the repeater to see an improvement in performance. Multiple phones and other handheld devices throughout a building can benefit from a wireless repeater.
- ▶ Supports up to (40) users / calls simultaneously.
- Extended phone battery life. (Your phone does not need to put out as much power due to improved reception.)
- No more running outside or near windows to complete your calls or receive pages.



# Wide dual band in any two of CDMA, GSM, DCS, WCDMA,PCS

## > Specification

#### **Electrical Specification**

Frequency Range		
CDMA	UL:824~849MHz	DL:869~894MHz
GSM850	UL:824~849MHz	DL:869~894MHz
GSM	UL:890~915MHz	DL:935~960MHz
DCS	UL:1710~1785MHz	DL:1805~1880MHz
PCS	UL:1850~1910MHz	DL:1930~1990MHz
WCDMA	UL:1920~1980MHz	DL:2110~2170MHz
Bandwidth	Wide band	
Maximum Gain	55dB	
Auto Level Control	20dB	
Output Power	10dBm	
Spurious Emission	-36dBm (9KHz~1GHz)	
	-30dBm (1GHz~12.75GHz)	
Noise Figure	6dB(Typical)	
Group Delay	1.5uS	

#### **Mechanical Specification**

Impedance 50 ohm  Dimensions (W x H x D) 218x134x57mm  Weight 1Kg  Operating Temperature -5 ~50  Environment Conditions IP40  Switch Adapter Input AC 90~264V	I/O Port	N-Female	
Weight 1Kg Operating Temperature -5 ~50 Environment Conditions IP40	Impedance	50 ohm	
Operating Temperature -5 ~50 Environment Conditions IP40	Dimensions (W x H x D)	218x134x57mm	
Environment Conditions IP40	Weight	1Kg	
	Operating Temperature	-5 ~50	
Switch Adapter Input AC 90~264V	Environment Conditions	IP40	
	Switch Adapter	Input AC 90~264V	

### > Models

Model 1: C10-CP (1 wide band in CDMA, 1 wide band in PCS)

Model 2: C10-GD (1 wide band in GSM, 1 wide band in DCS)

Model 3: C10-GW (1 wide band in GSM, 1 wide band in WCDMA)

Model 4: C10-CW (1 wide band in CDMA, 1 wide band in WCDMA)