

LAN Phone 399

Multi-Lines IP Phone Solution



Welltech LAN Phone 399 is a full-featured IP desktop telephone set. For ease-of-use functionality and ergonomic design, home user or enterprise can integrate this state-of-the-art phone into daily life. With affordable price, Welltech LAN Phone 399 represents cost savings and convenience.

Built-in 2 Ethernet ports allows user to connect PC or network device directly through LAN phone without extra Hub. With NAT function, LAN Phone 399 can also allow user to access Internet without additional public IP.

Based on innovative technology, Welltech LAN Phone 399 built-in many user-friendly feature buttons, including HOLD, TRANSFER, REDIAL, CONFERENCE, CALL PICK UP, SPEED dial...etc. With high-quality speakerphone, user can enjoy VoIP more conveniently. It is no doubt LAN Phone 399 will be the best choice for everyone with VoIP.

Application

- ISP/ITSP (Internet Telephony Service Provider)
- IP-PBX with office telephony services
- Multi-nation enterprise communication
- SOHO Telephony

Calling Features

- Call Hold
- Call Transfer
- Call Forward
- Call Waiting
- Call Conference
- DND (Do Not Disturb)
- Call List (Missed, Received, Dialed)
- 2 configurable speed dials
- Support up to 3 multi-lines

Network Support

- Fixed IP
- Dynamic Host Configuration Protocol (DHCP)
- PPPoE connection
- Support QOS by setting DSCP (Differentiated Service Code Point) parameters of VoIP packet
- Support NAT function
- Support STUN Function

Technical Specification

- Two 10/100 Base-T Ethernet ports with Switch or NAT inside
- LCD Configuration Password Protection
- 2x16 character LCD display
- LCD Display Time, Date, Caller ID, Call Duration

Audio Features

- G.711 A/µ-Law, G.729, G.726
- Provide In-band and Out-band DTMF generation/detection

Provisioning and Configuration

- SIP (RFC3261) compliance
- LCD configuration password protection
- Provide adjustable Ringer , Speaker and Handset volume
- Support DNS server inquiry



Management Features

- Software Upgrade: TFTP download
- Easy ways for system configuration
 - A. LCD Front Panel
 - B. Web Browser
 - C. TELNET
 - D. Provision Server

Certification

CE, FCC

Power Supply

DC12V output adaptor, AC 100-240Vac input

Operation Environment

- Humidity: 10 to 90 % (Non-condensing)
- Operational Temperature: 0 to +40°C

Storage Environment

- Humidity: 10 to 90 % (Non-condensing)
- Storage Temperature: -10 to +50°C

LAN Phone-399 Application Diagram:

