



WELLTECH

WellGate 3701A/ 3702A FXS+FXO

Converging PSTN and VoIP services into One Network



WellGate3701A/3702A

WellGate 3701A/3702A is a one-port/two-port FXS + FXO gateway. It supports an innovative intelligent call routing function that transparently routes calls to destination either through PSTN or Internet.

WellGate 3701A/3702A provides Voice over IP and FAX over IP services for ITSP / ISP Internet Telephony Services Provider and Office / SOHO IP-PBX application.

WellGate 3701A/3702A supported H.323 v2/v3/v4 and SIP protocol. It also provides various voice codec i.e. G.711A/μ-Law, G.723.1, G.729 and G.729A with Dynamic Jitter Buffer and Bad frame interpolation.

Application

- ISP/ITSP (Internet Telephony Service Provider)
- Multi-nation enterprise communication
- SOHO Telephony
- IP-PBX with office telephony services
- Telephone /PBX call via IP network
- FAX over IP (FoIP) device



Benefits

- Easy access to IP from phone set or PBX
- Cost Saving - Telephone call from VPN or public Internet
- Follows the existing telephone call dial plan
- Easy interface with ADSL/Cable Modem and Leased line equipment

Dimensions: 223mm(W)*35mm(H)*152mm(D)
Weight (unit): 1.5 kg



Rear Panel Drawing



Features

- ITU-T H.323 v2/v3/v4 compliance
 - Support SIP protocol
 - Automatically Dial Path Selection (IP or PSTN)
 - PSTN Line switch to telephone set when power is failure.
 - PPPoE
 - Behind NAT router or IP sharing device
 - DNS server inquiry
 - Automatically Gatekeeper Discovery
 - Provide Peer-to-Peer Mode (Non Gatekeeper needed) selection
 - E.164 Dial Plan
 - DTMF detection/generation
 - TFTP/FTP software upgrade
 - Remote configuration/reset
 - LED indication for system status
 - MS-NetMeeting v3.0 compatible
 - Support Fix IP and DHCP
 - Parameters of VoIP packet
 - MGCP (**)
- (**) : Contact Welltech for availability

Audio Feature

- Codec -- G.711 A/ μ -Law, G.723.1, G.729A, G.729
- G.168/165-compliant adaptive echo cancellation
- Dynamic Jitter Buffer
- Completed voice band signaling support
- Provide In-band or Out-band DTMF generation/detection
- Provide call progress tone

FAX Support

- Provide T.38/FAX function

FXS features

- Line polarity reversal generation
- 2-wire loop start
- Caller ID (DTMF/FSK) generation
- Programmable On-Hook voltage, Ring voltage/Cadence/Frequency, Loop Current

FXO features

- 2-wire loop start
- Support auto-attendant (Tone or voice greeting)
- PSTN polarity reversal detection
- Provide 2nd dial tone to PSTN
- Disconnect tone detection

Technical Specification

Interface

- Two 10/100Base-T Ethernet RJ-45 port
- One DB-9 RS-232 COM port
- One Analog PSTN (FXO) RJ-11 port and One Telephone (FXS) RJ-11 port for WellGate 3701A only.
- Two Analog PSTN (FXO) RJ-11 ports and Two Telephone (FXS) RJ-11 ports for WellGate 3702A only.
- DC 12V input (Provide external AC100-240Vac input adaptor)

Management Feature

- TELNET/Console port and Web Browser configuration

Certification

- UL, CE, FCC

LED indicators for system status

- POWER: Power ON indication
- TEL1 to TEL2: LED indicator for Telephone port status (FXS)
- LINE1 to LINE2: LED indicator for PSTN port 1-2 status (FXO)
- STATUS: WellGate 3701A/3702A register to Gatekeeper status
- READY: WellGate 3701A/3702A operation status
- WAN: - LINK / ACT: Link and Active status - 10/100: 10 or 100Base-T status
- LAN: - LINK / ACT: Link and Active status - 10/100: 10 or 100Base-T status


Power

- Input AC 100V~240V Output DC12V.

Environmenta

- Operation temp: 0° C to 40° C
- Humidity: 10% to 90% (Non-condensing)

Application Diagram



Welltech Computer Co., Ltd.
13F-4, No.150, Jian Yi Road,
Chung-Ho, Taipei, Taiwan
Tel: +886-2-82265699
Fax: +886-2-82265799
E-mail: sales@mail.welltech.com.tw
Http://www.welltech.com.tw